

TECHNICAL 10 Plus

Cat. no: DT-0010-DJA



**Technical specification:**

- Works under tap water pressure.
- Water purification process levels:
 - sediment pre-filter 5µm,
 - integrated module (sediment-carbon-softening) – module A,
 - reverse osmosis,
 - demineralization on a mixed ion-exchange bed.
- Device efficiency: 10 dm³/h.
- Equipped with a pump (increasing the feed water pressure) with automatics.
- Retention level: 97-99%.
- Unattended and automated.
- One water intake point second/third class (ISO 3696:1999, ASTM).
- Purified water conductivity with optional regulation between 0,06 µS/cm and 15,00-20,00 µS/cm (the largest value depends on the quality of feed water).
- Mobile, adjustable inox arm holding water collection points – available adjustment ranges: up/down, front/back, left/right
- Possibility of equipment with a pressure tank.
- Automatic system shutdown when the tank is full or the filtrate valve is closed.
- Optional connection to a washer, an autoclave etc.
- May be used for making a demi water network with several water intake points.
- Maintenance procedures may be performed by the user (easy disposables replacement).
- Fed by cold water: 5-40°C.
- Power supply: 230V/50Hz.
- Can be installed by the user.

Dimensions: 235x470x570 mm

Functions monitoring the device:

- The device is equipped with a microprocessor control and measurement system that includes:
 - LCD display screen 2x16 characters
 - conductometer measuring conductivity and temperature of purified water (measured in µS/cm or MOhm),
 - reading values compensated and uncompensated thermally,
 - timer displaying current date and time,
 - information about the membrane module retention level,
 - alarm informing about necessity to replace sediment filter and module A,
 - alarm informing about necessity to replace RO module,
 - alarm informing about the necessity to replace the ion-exchange cartridge,
 - alarm informing about necessity to replace UV lamp (option),
 - maintenance deadlines preview,
 - built-in RS 232 connector for personal computers,
 - individual adjustment of maintenance frequency and alarm levels.
- Software.
- Built-in manometer measuring feed water pressure.


Functions protecting the device:

- Pump shutdown when:
 - feed water pressure is too low (lack of feed water) – low pressure sensor,
 - the tank is full – high pressure sensor.

- Conductivity < 1200 µS/cm
- Pressure > 3,0 bar
- Temperature: 5-40°C
- Hardness < 250 mg CaCO₃/dm³
- Fe < 0,2 mg/dm³

Purity class:

Demineralized water fits the ISO 3696:1999
 A standard for II and III class of water purity

**Usage:**

May be used for mediums, buffer solutions, reagents.
 Can supply other laboratory devices: washers, analyzers, autoclaves, Ultra systems etc.

Required connections:

- cold tap water connection ½" lub ¾",
- 230V socket,
- drain.

Model TECHNICAL	Sediment prefilter 5µm	Module A	Module H6	UV lamp radiator
TECHNICAL 10 Plus	+	+	+	option
Lifetime	6 months*	6 months*	5000 dm ³ */***	8500 h**
Cataloge no.	EO-005-10	EO-MA-12	EJ-5000-0	EUV-254-HLP

* Filter usage depends on the quality of feed water and on the amount of water collected. We do not recommend storing the filter longer than 4 months

** lifetime 12 months or 8500 hours

*** lifetime depends on the conductivity adjustment