

TECHNICAL 30/C Plus

Cat. no: DT-0030-DJC





Technical specification:

- Works under tap water pressure.
- Water purification process levels:
 - sediment pre-filter 5µm,
 - integrated module (sediment-carbon-softening) – module A,
 - reverse osmosis,
 - demineralization on a mixed ion-exchange bed.
- Device efficiency: 30 dm³/h.
- Equipped with a pump (increasing the feed water pressure) with automatics.
- Retention level: 97-99%.
- Unattended and automated.
- One water intake point second/third class (ISO 3696:1999, ASTM).
- Purified water conductivity with optional regulation between 0,06 µS/cm and 15,00-20,00 µS/cm (the largest value depends on the quality of feed water).
- Mobile, adjustable inox arm holding water collection points – available adjustment ranges: up/down, front/back, left/right
- Possibility of equipment with a pressure tank.
- Automatic system shutdown when the tank is full or the filtrate valve is closed.
- Optional connection to a washer, an autoclave etc.
- May be used for making a demi water network with several water intake points.
- Maintenance procedures may be performed by the user (easy disposables replacement).
- Fed by cold water: 5-40°C.
- Power supply: 230V/50Hz.
- Can be installed by the user.

Dimensions: 235x470x570 mm

Functions monitoring the device:

- The device is equipped with a 24V automatics with a microprocessor control and measurement system, that includes:
 - color display screen with a Touch Panel,
 - conductometer measuring conductivity and temperature of feed water and after reverse osmosis (measured in µS/cm or MΩm),
 - reading values compensated and uncompensated thermally,
 - clock displaying date and time,
 - information about current system status,
 - information about the membrane module retention level,
 - alarm informing about necessity to replace module A,
 - alarm informing about necessity to replace RO module,
 - alarm informing about the necessity to replace the ion-exchange cartridge,
 - alarm informing about necessity to replace UV lamp (option),
 - graphic and sound alarm signal,
 - maintenance dates preview,
 - tank fill level,
 - built-in RS 232 connection to personal computers allowing to adjust maintenance frequency and alarm levels,
 - built-in USB connection to personal computers allowing to adjust maintenance frequency and alarm levels.
- Software.
- Built-in manometer measuring feed water pressure.

Functions protecting the device:

- Pump shutdown when:
 - the feed water pressure is too low (lack of feed water) - low pressure sensor,
 - the tank is full - high pressure sensor.
- Thermal protection of the RO module, automated system shutdown when the feed water temperature is below 4°C or above 40°C.
- Can be automatically shut down when any alarm occurs.
- System autostart.
 - Conductivity < 1200 µS/cm
 - Pressure > 3,0 bar
 - Temperature: 5-40°C
 - Hardness < 250 mg CaCO₃/dm³
 - Fe < 0,2 mg/dm³

**Purity class:**

Demineralized water fits the ISO 3696:1999
A standard for II and III class of water purity

Usage:

May be used for mediums, buffer solutions, reagents.
Can supply other laboratory devices: washers, analyzers, autoclaves, polishing systems etc.

Required connections:

- cold tap water connection 1/2" lub 3/4",
- 230V socket,
- drain.

Model	Sediment prefilter 5µm	Module A	Module H6	UV lamp radiator
TECHNICAL 30/C Plus	+	+	+	option
Lifetime	6 months*	6 months*	5000 dm3*/***	8500 h
Cataloge no.	EO-005-10	EO-MA-12	EJ-5000-0	EUV-254-HLP

* Filter usage depends on the quality of feed water and on the amount of water collected. We do not recommend storing the filter longer than 4 months

** lifetime 12 months or 8500 hours

*** lifetime depends on the conductivity adjustment